IOWA FFA AGRICULTURAL MECHANICS CAREER DEVELOPMENT EVENT WRITTEN EXAMINATION IOWA STATE UNIVERSITY AMES, IOWA JUNE 7, 2007

MACHINERY and EQUIPMENT SYSTEMS

1. At the present time, there are _____ GPS satellites visible from where you are seated.

- a) 1
- b) 2
- c) 4
- d) 6
- 2. A GPS monitor is located in _____.
 - a) Boulder, Colorado
 - b) Phoenix, Arizona
 - c) Colorado Springs, Colorado
 - d) Houston Space Center, Texas

3. Real Time Kinematic (RTK) GPS systems can provide ______ accuracy.

- a) 2 meter
- b) 1 meter
- c) 500 cm
- d) Sub-inch

4. Class _____ combines, such as the 9860STS or A85 Gleaner, will be able to handle 16 row corn heads.

- a) IV
- b) V
- c) VII
- d) VIII
- 5. Transverse rotor combines have the rotor placed ______.
 - a) crosswise to the length of the combine
 - b) lengthwise to the combine
 - c) vertically to the combine
 - d) none of the above
- 6. Combine fires can be prevented by all of the following, except:
 - a) a fire extinguisher placed outside the cab door
 - b) cleaning the trash out of the engine compartment on a regular basis.
 - c) preventing oil leaks
 - d) after shutting down the combine, and stopping the engine, check all the bearings for overheating.
- 7. Differential GPS stationary receivers are located at ______ and _____.
 - a) Iowa City, IA and Cedar Rapids, IA
 - b) Iowa City, IA and Ames, IA
 - c) Bettendorf, IA and Davenport, IA
 - d) Ledyard, IA and Iowa City, IA

- _____ is a common name for multi-path GPS errors.
- a) ephemeris

8.

- b) error correction
- c) ghosting
- d) double vision
- 9. Add-on auto-steer systems, such as the John Deere Autotrac Universal, use a ______ to steer the tractor, sprayer or combine.
 - a) hydraulic motor
 - b) powered rubber wheel that contacts the steering wheel hub
 - c) computer connected to stepper motors on the axle
- 10. Current John Deere combines have a _____ rotor.
 - a) longitudinal
 - b) transverse
 - c) diagonal
 - d) down front
- 11. All of the following are good safety practices to follow when operating a combine, except:
 - a) always obey traffic laws when operating on the highway
 - b) run down the steps from the cab if you are in a hurry
 - c) keep flashing lights, SMV emblems and mirrors in good condition
 - d) take a break for a few minutes if you get sleepy
- 12. If you are following a combine, and the left flashing light is a steady light, and the right light continues to flash, it indicates:
 - a) the combine operator is going to make a left turn
 - b) the left flasher has probably failed and you can ignore it
 - c) the combine operator is going to make a right turn
 - d) the combine operator is slowing down the machine

ENVIRONMENT AND NATURAL RESOURCE SYSTEMS

- 13. The dominant form of water erosion in agricultural areas of the United States is ______ erosion.
 - a) pasture
 - b) sheet
 - c) blanket
 - d) landslide
- 14. Following a heavy rain, less runoff will occur in a field that is well tiled because of:
 - a) finer soil textures
 - b) flatter field slopes
 - c) greater available soil moisture storage capacity
 - d) more crop cover
- 15. _____ is a term used to describe the level of soil acidity.
 - a) "sa"
 - b) "pH"
 - c) HCl
 - d) None of the above

- 16. The ______ is a method used to estimate the rate of soil loss in a given area, considering several variables.
 - a) Universal Soil Loss Equation
 - b) Universal Soil Erosion Formula
 - c) United States Soil Movement Formula
 - d) Universal Soil Conservation Formula
- 17. There should be ______ % residue coverage left on the surface of a minimum- tilled, continuous corn field.
 - a) 0
 - b) 10
 - c) 75
 - d) 90
- 18. All of the following statements concerning Fall chisel plowing of soybean ground are true, except:
 - a) it is not recommended in Iowa because of severe problems with soil erosion in hilly parts of the state
 - b) it is a good way to get a head start on next year's tillage and is a recommended practice
 - c) it is the cause of soil erosion, because soybeans tend to "loosen" the soil
 - d) it destroys the limited soil cover available from soybean residue
- 19. Applying manure to a field with ______ will result in the most residue left on the field to minimize runoff.
 - a) a manure spreader then disking the field
 - b) a spreader then moldboard plowing
 - c) injecting the manure with sweep points on the injectors
 - d) injecting the manure with chisel points on the injectors
- 20. Parallel terraces can give all of the following benefits, except:
 - a) maximum machine efficiency will be achieved
 - b) the work ground will tend to be more level
 - c) there will be more point rows
 - d) there will be less point rows
- 21. _____ is a source of nonpoint pollution of water supplies.
 - a) sediment from croplands
 - b) feedlots
 - c) confinement milking setups
 - d) pesticide disposal sites

22. Land put in the Conservation Reserve Program will require:

- a) regular cultivation
- b) growing row crops
- c) regular heavy pesticide applications
- d) mowing selected areas of the field, as necessary, to control noxious weeds
- 23. A ______ is the area on either side of a stream, planted to control runoff into the stream.
 - a) grassy plain
 - b) riparian buffer
 - c) agricultural buffer
 - d) riparian plain

- 24. The initials NRCS stand for:
 - a) National Republic Congressional Statute
 - b) National Resource Control System
 - c) Natural Resources Conservation Service
 - d) Natural Resources Continuum Society

INDUSTRY AND MARKETING SYSTEMS

- 25. All of the following are good safety practices when operating a small engine, except:
 - a) wear tight fitting clothing which is in good condition
 - b) stay clear of hot areas on the engine
 - c) operate the engine in a well-ventilated area
 - d) wear loose-fitting jeans with frayed knees
- 26. If you have hit a rock with the push-type lawn mower blade, all of the following are possible outcomes, except:
 - a) the engine power will increase
 - b) the crankshaft could be broken
 - c) the timing could be late and cause a loss of power
 - d) the engine crankcase could be cracked
- 27. OHSA requires the lawn mower blade to stop in ______ seconds if the safety bar on the handle of a push-type lawn mower is released.
 - a) 28
 - b) 20
 - c) 3
 - d) 0.01

28. If a lawn mower strikes a rock, it could be propelled by the blades at speeds up to _____ MPH.

- a) 200
- b) 100
- c) 10
- d) 5

29. On a diesel small engine, ______ is compressed on the compression stroke.

- a) air and gasoline
- b) air and diesel fuel
- c) air only
- d) diesel fuel
- 30. On a diesel small engine, ______ is the ignition source.
 - a) compression due to heat
 - b) a spark
 - c) heat due to compression
 - d) an auxiliary ignition source
- 31. The choke on a small engine:
 - a) enriches the air-fuel mixture entering the combustion chamber
 - b) leans out the air-fuel mixture entering the combustion chamber
 - c) allows less fuel into the combustion chamber
 - d) allows more air to enter the combustion chamber

- 32. The key switch stops a small gasoline engine(equipped with a magneto) by:
 - a) removing the power to the ignition system
 - b) grounding the ignition circuit
 - c) reversing the current flow in the ignition circuit
 - d) cutting off the fuel supply
- 33. 10% ethanol-gasoline blends can be used in:
 - a) all recently manufactured small gasoline engines
 - b) only engines manufactured by Briggs and Stratton
 - c) any engines not manufactured in Japan
 - d) only engines with 18 or more horsepower
- 34. You can always find the recommended engine oil to use in your lawn and garden tractor by:
 - a) looking at the engine data plate
 - b) looking in the parts book
 - c) looking in the operator's manual
 - d) contacting Wal-Mart only
- 35. All of the following statements are correct, except:
 - a) you should follow the manufacturer's recommendations for correct oil viscosity
 - b) all small engines can use the same type of oil
 - c) 4-cycle engines do not have oil mixed in the gasoline
 - d) small 2-cycle engines generally do not have oil in a crankcase
- 36. _____ fumes can be noxious or fatal, if a small engine is operated in a confined space.
 - a) carbon dioxide
 - b) oxygen
 - c) ozone
 - d) carbon monoxide

ENERGY SYSTEMS

- 37. If a person is being shocked by a 115 volt electrical circuit, you should first:
 - a) administer CPR
 - b) phone 911
 - c) shut off the circuit
 - d) call the fire department
- 38. If you wanted to have a fan, used to control temperature in stored grain, turn off at temperatures at or below 40 degrees, you would use a:
 - a) normally closed (NC) thermostatic switch that opens on temperature decrease
 - b) normally closed (NC) thermostatic switch that opens on temperature increase
 - c) humidistat
 - d) pressure switch
- 39. All of the following are requirements for components used in a grain drying and storage set-up, except:
 - a) explosion-proof light fixtures
 - b) open frame motors
 - c) sealed explosion-proof motors
 - d) properly grounded electrical components

- 40. ______ is the instrument used to measure continuity in an electrical circuit.
 - a) voltmeter
 - b) ammeter
 - c) potentiometer
 - d) ohmmeter

41. If an electrical wire is broken in a circuit, this fault is described as a(n):

- a) ground
- b) short
- c) open
- d) crossover

42. A device that uses a small electrical current to control a large electrical current, is called a(n):

- a) relay
- b) capacitor
- c) transformer
- d) inverter

43. If you need to fasten 4 wires together in a junction box, you would:

- a) fasten all 4 wires together with 1 wire nut
- b) fasten 3 wires together with a pigtail, and then fasten the pigtail to the other wire with a second wire nut
- c) fasten 2 wires together with a pigtail, then fasten the other 2 wires together with a pigtail and a wire nut, and then fasten the 2 pigtails together with a wire nut
- d) twist all 4 wires together and cover them with a generous amount of black tape
- 44. If you are going to work on the electrical circuit of a a grain drying setup, you should turn off the electrical circuit and:
 - a) put a lockout device on the control box
 - b) work fast so that you get done before someone turns the circuit back on
 - c) leave the box cover open so that others will know that you are working on the circuit
 - d) hire an extra person to stand guard at the control box

45. ______ is the correct way to hook up the wires in an electrical circuit.

- a) bare to green screw, white to chrome screw, black to brass screw
- b) bare to chrome screw, white to green screw, black to brass screw
- c) bare to circuit enclosure, white to chrome screw, black to brass screw
- d) black to brass screw, white and bare to chrome screw
- 46. Present electrical circuits have _____ volts.
 - a) 110 or 240
 - b) 115 or 220
 - c) 115 or 230
 - d) 115 or 250
- 47. A GFCI is a:
 - a) ground fault checking integrated circuit
 - b) ground fault circuit interrupter
 - c) ground finding circuit interrupter
 - d) none of the above

- 48. An aeration fan on a grain bin would be most economical to run :
 - a) whenever it is below 12 degrees F.
 - b) whenever there is humidity in the air
 - c) as needed, when the air temperature is above freezing
 - d) all the time

STRUCTURAL SYSTEMS

49. Based on 1.245 cubic feet per bushel, a 30 ft. diameter grain bin, 20 ft. tall, would hold this many bushels:

a) 11,305 b) 45,000 c) 10,220 d) 22,222	FormulaRBC= (0.785) x (D) x (D) x (H) x (0.8)whereRBC = Round Bin Capacity0.785 = a constant = $\pi/4$ D = bin diameter in feetH = bin height in feet

0.8 = conversion factor(cu. ft. to Bu.)

50. joints in a grain bin are better able to withstand extreme rapid temperature changes in an Iowa winter.

- a) welded
- b) brazed
- c) fusion welded
- d) bolted

51. The slump test determines

- a) flow ability of concrete, indicating water content
- b) the sand content of the concrete mix
- c) engineered form factor X
- d) the identification of the source of the concrete
- 52. _____ comes in the sack and _____ is the material placed in the form.
 - a) concrete, cement
 - b) readymix, cement
 - c) cement, concrete
 - d) sackcrete, cement

53. Hydration is the chemical process that forms:

- a) concrete
- b) cement
- c) readymix
- d) none of the above
- 54. 1-2-3, are the numbers to remember when mixing concrete. These numbers indicate:
 - a) 1 part sand, 2 parts cement, 3 parts crushed limestone
 - b) 1 part cement, 2 parts sand, 3 parts crushed limestone
 - c) 1 part crushed limestone, 2 parts cement, 3 parts, sand
 - d) none of the above
- 55. All of the following are good safety practices to use when unloading a round steel grain bin, except:
 - a) never enter the bin when it is being unloaded
 - b) keep children safely away from the grain bin
 - c) only allow adults to enter the grain bin while it is being unloaded
 - d) know the whereabouts of everyone in the area of the bin

- 56. A crust can be formed on top of a bin full of stored grain. All of the following are true, except:
 - a) the crust can remain in place, even though the grain below the crust has been partially removed
 - b) the crust will fall in as soon as you start to remove the grain
 - c) it is absolutely unsafe to walk on the grain crust
 - d) the crust was formed due to grain and storage conditions
- 57. All of the following are good safety practices to use when working around grain bins, except:
 - a) never enter a grain bin while it is being unloaded
 - b) if fumigants have been used in a grain bin, always allow sufficient air flow through the bin before attempting to enter the bin
 - c) attach a large knotted rope to the center top of the bin and let it hang down into the bin as a possible way for someone to grab hold in case they get caught in a grain spiral
 - d) only allow someone to enter the bin while it is being unloaded if they are properly supervised
- 58. Grain dust explosions are:
 - a) not possible in a bin that has been grounded
 - b) an unlikely hazard that can be ignored
 - c) a hazard associated with filling a bin or removing stored grain from a bin
 - d) can only happen during the summer
- 59. All of the following statements are true concerning grain stored in a pile on the ground back of the local Co-op except:
 - a) grain should be checked regularly for insect damage, mold and moisture content
 - b) grain is assumed to be in good condition unless you smell spoilage
 - c) grain moved or delivered before warm weather occurs
 - d) grain should be covered, if possible
- 60. Corn weighs _____ pounds per bushel.
 - a) 30
 - b) 45
 - c) 56
 - d) 70

2007 AGRICULTURAL MECHANICS CAREER DEVELOPMENT EVENT WRITTEN TEST ANSWER KEY IOWA STATE UNIVERSITY AMES, IOWA JUNE 7, 2007

60. C

1. C 2. C 3. D 4. D 5. A 6. A	31. A 32. B 33. A 34. C 35. B 36. D
7. D	37. C
8. C	38. A
9. B	
10. A	39. B
11. B	40. D
12. C	41. C
13. B	42. A
14. C	43. C
15. B	44. A
16. A	45. A
17. C	46. C
18. B	47. B
19. D	48. C
20. C	49. A
21. A	50. D
22. D	51. A
23. B	52. C
24. C	53. A
25. D	54. A
26. A	55. C
27. C	56. B
28. A	57. D
29. C	58. C
30. C	59. B

CONTESTENT NAME _____

CONTESTANT SCHOOL _____

COMPUTER APPLICATION Grain Unloading Capacity

Use the provided Excel computer spreadsheet to assist in determining the corn grain unloading conveyor capacity for a grain center. Relevant pages from MWPS-13 (Grain Drying, Handling and Storage Handbook) are provided as reference if needed. Instructions:

- 1. Enter your name and school into the computer spreadsheet.
- 2. Enter the given data and formulas to determine the grain unloading conveyor capacity (UC).
- 3. Print out the completed spreadsheet.
- 4. Change the data for the new scenarios and answer the specified questions.
- 5. Staple this sheet to your printout and turn into the judge.

Given (enter data into spreadsheet):	Enter formula into spreadsheet using cell references
• Harvest width (W) = 15 ft	• Effective Field Capacity (EFC) = (W)(S)(e)/8.25 ac/hr
• Speed (S) = 4.0 mph	• Maximum harvest rate (MHR) = (EFC)(Y) bu/hr
• Harvest efficiency (e) $= 0.70$	
• Corn yield (Y) = 180 bu/ac	Spreadsheet Output (calculated by spreadsheet):
• Capacity of largest vehicle (LV) = 850 bu	• Travel time from field to grain center - largest vehicle (TTG)
• Capacity of smallest vehicle (SV) = 500 bu	• Travel time return to field – largest vehicle (TTR)
• Farthest distance – field to grain center (FD) = 1.1 miles	• Time to fill smallest vehicle (Sfill)
• Average travel speed for largest vehicle when fully loaded	• Time available for largest vehicle to unload largest vehicle
$(VL_{full}) = 20$ mph.	(AUT)
• Average travel speed for largest vehicle when empty	• Unloading conveyor capacity (UC)
$(VL_{empty}) = 35$ mph.	
• Miscellaneous activities (TMA) = 7 min	
• Actual pit capacity $(PC_a) = 450$ bu	

NEW SCENARIOS - QUESTIONS:

1.	What is the required unloading conveyor capacity (UC) if the distance to the farthest field increases to 2.5 miles due to a land purchase? Is this an increase or decrease?	UC = bu/hr \Box Increase \Box Decrease
2.	What is the required unloading conveyor capacity (UC) if the harvesting is done with an 8-row combine (W=20 ft) instead of a 6-row combine (W=15 ft)? Is this is an increase or decrease?	UC = bu/hr \Box Increase \Box Decrease
3.	What is the required unloading conveyor capacity (UC) if vehicle loading switched from field's end ($e=0.7$) to on-the- go ($e=0.8$)? Is this an increase or decrease?	UC = bu/hr \Box Increase \Box Decrease

	Evaluation Scole Shot	~~	
	<u>Item</u>	Poi	ints
		Possible	Earned
1.	Data entered correctly	11	
2.	Formulas entered correctly	6	
2	Computer printouts	2	
	New scenario questions		
		AL 25	

CONTESTENT NAME _____ANSWER KEY_____

CONTESTANT SCHOOL _____

COMPUTER APPLICATION Grain Unloading Capacity

Use the provided Excel computer spreadsheet to assist in determining the corn grain unloading conveyor capacity for a grain center. Relevant pages from MWPS-13 (Grain Drying, Handling and Storage Handbook) are provided as reference if needed. Instructions:

- 1. Enter your name and school into the computer spreadsheet.
- 2. Enter the given data and formulas to determine the grain unloading conveyor capacity (UC).
- 3. Print out the completed spreadsheet.
- 4. Change the data for the new scenarios and answer the specified questions.
- 5. Staple this sheet to your printout and turn into the judge.

Given (enter data into spreadsheet):	Enter formula into spreadsheet using cell references
• Harvest width (W) = 15 ft	• Effective Field Capacity (EFC) = $(W)(S)(e)/8.25$ ac/hr
• Speed (S) = 4.0 mph	• Maximum harvest rate (MHR) = (EFC)(Y) bu/hr
• Harvest efficiency (e) = 0.70	
• Corn yield (Y) = 180 bu/ac	Spreadsheet Output (calculated by spreadsheet):
• Capacity of largest vehicle (LV) = 850 bu	• Travel time from field to grain center - largest vehicle (TTG)
• Capacity of smallest vehicle (SV) = 500 bu	• Travel time return to field – largest vehicle (TTR)
• Farthest distance – field to grain center (FD) = 1.1 miles	• Time to fill smallest vehicle (Sfill)
• Average travel speed for largest vehicle when fully loaded	• Time available for largest vehicle to unload largest vehicle
$(VL_{full}) = 20$ mph.	(AUT)
• Average travel speed for largest vehicle when empty	• Unloading conveyor capacity (UC)
$(VL_{empty}) = 35$ mph.	
• Miscellaneous activities (TMA) = 7 min	
• Actual pit capacity $(PC_a) = 450$ bu	

NEW SCENARIOS - QUESTIONS:

1.	What is the required unloading conveyor capacity (UC) if the distance to the farthest field increases to 2.5 miles due to a land purchase? Is this an increase or decrease?	UC =	1720	bu/hr	☑ Increase □ Decrease
2.	What is the required unloading conveyor capacity (UC) if the harvesting is done with an 8-row combine (W=20 ft) instead of a 6-row combine (W=15 ft)? Is this is an increase or decrease?	UC =	1941	bu/hr	☑ Increase □ Decrease
3.	What is the required unloading conveyor capacity (UC) if vehicle loading switched from field's end ($e=0.7$) to on-the- go ($e=0.8$)? Is this an increase or decrease?	UC =	1458	bu/hr	☑ Increase □ Decrease

	Evaluation Scole Shee		
	<u>Item</u>	<u>Pc</u>	<u>oints</u>
		Possible	Earned
1.	Data entered correctly	11	
2.	Formulas entered correctly	6	
2	Computer printouts	2	
	New scenario questions		
		AL 25	

Name:	ANSWER KEY FOR PRINTOUT
School:	

Parameter	Symbol	Units	Value	Comment
Harvest width	W	ft	15	Enter data from instruction sheet
Average harvest speed	S	mph	4.0	Enter data from instruction sheet
Harvest efficiency	е	decimal	0.7	Enter data from instruction sheet
Effective Field Capacity	EFC	ac/hr	5.1	Enter formula in cell D10 using cell references
Corn Yield	Y	bu/ac	180	Enter data from instruction sheet
Maximum Harvest Rate	MHR	bu/hr	916.4	Enter formula in cell D12 using cell references
Largest Vehicle Capacity	LV	bu	850	Enter data from instruction sheet
Smallest Vehicle Capacity	SV	bu	500	Enter data from instruction sheet
Farthest distance - field to grain center	FD	miles	1.1	Enter data from instruction sheet
Average travel speed - largest vehicle (full)	VL _{full}	mph	20	Enter data from instruction sheet
Average travel speed - largest vehicle (empty)	VL _{empty}	mph	35	Enter data from instruction sheet
Travel time to grain center - largest vehicle	TTG	min	3.3	Calculated results
Travel time return to field - largest vehicle	TTR	min	1.9	Calculated results
Miscellaneous activity time	TMA	min	7	Enter data from instruction sheet
Time to fill the smallest vehicle	Sfill	min	32.7	Calculated results
Time available to unload largest vehicle	AUT	min	20.6	Calculated results
Pit capacity	PCa	bu	450	Enter data from instruction sheet
Unloading capacity	UC	bu/hr	1,168	Calculated results

Color	Key	
-------	-----	--

y Enter data from instruction sheet Enter formula using cell references Calculated results

Name:	ANSWER KEY FOR SCENARIO #1
School:	

Parameter	Symbol	Units	Value	Comment
Harvest width	W	ft	15	Enter data from instruction sheet
Average harvest speed	S	mph	4.0	Enter data from instruction sheet
Harvest efficiency	е	decimal	0.7	Enter data from instruction sheet
Effective Field Capacity	EFC	ac/hr	5.1	Enter formula in cell D10 using cell references
Corn Yield	Y	bu/ac	180	Enter data from instruction sheet
Maximum Harvest Rate	MHR	bu/hr	916.4	Enter formula in cell D12 using cell references
Largest Vehicle Capacity	LV	bu	850	Enter data from instruction sheet
Smallest Vehicle Capacity	SV	bu	500	Enter data from instruction sheet
Farthest distance - field to grain center	FD	miles	2.5	Enter data from instruction sheet
Average travel speed - largest vehicle (full)	VL _{full}	mph	20	Enter data from instruction sheet
Average travel speed - largest vehicle (empty)	VL _{empty}	mph	35	Enter data from instruction sheet
Travel time to grain center - largest vehicle	TTG	min	7.5	Calculated results
Travel time return to field - largest vehicle	TTR	min	4.3	Calculated results
Miscellaneous activity time	TMA	min	7	Enter data from instruction sheet
Time to fill the smallest vehicle	Sfill	min	32.7	Calculated results
Time available to unload largest vehicle	AUT	min	14.0	Calculated results
Pit capacity	PCa	bu	450	Enter data from instruction sheet
Unloading capacity	UC	bu/hr	1,720	Calculated results

Color Key

Enter data from instruction sheet Enter formula using cell references Calculated results

Name:	ANSWER KEY FOR SCENARIO #2
School:	

Parameter	Symbol	Units	Value	Comment
Harvest width	W	ft	20	Enter data from instruction sheet
Average harvest speed	S	mph	4.0	Enter data from instruction sheet
Harvest efficiency	е	decimal	0.7	Enter data from instruction sheet
Effective Field Capacity	EFC	ac/hr	6.8	Enter formula in cell D10 using cell references
Corn Yield	Y	bu/ac	180	Enter data from instruction sheet
Maximum Harvest Rate	MHR	bu/hr	1221.8	Enter formula in cell D12 using cell references
Largest Vehicle Capacity	LV	bu	850	Enter data from instruction sheet
Smallest Vehicle Capacity	SV	bu	500	Enter data from instruction sheet
Farthest distance - field to grain center	FD	miles	1.1	Enter data from instruction sheet
Average travel speed - largest vehicle (full)	VL _{full}	mph	20	Enter data from instruction sheet
Average travel speed - largest vehicle (empty)	VL _{empty}	mph	35	Enter data from instruction sheet
Travel time to grain center - largest vehicle	TTG	min	3.3	Calculated results
Travel time return to field - largest vehicle	TTR	min	1.9	Calculated results
Miscellaneous activity time	TMA	min	7	Enter data from instruction sheet
Time to fill the smallest vehicle	Sfill	min	24.6	Calculated results
Time available to unload largest vehicle	AUT	min	12.4	Calculated results
Pit capacity	PCa	bu	450	Enter data from instruction sheet
Unloading capacity	UC	bu/hr	1,941	Calculated results

Color Key

Enter data from instruction sheet Enter formula using cell references Calculated results

Name:	ANSWER KEY FOR SCENARIO #3
School:	

Parameter	Symbol	Units	Value	Comment
Harvest width	W	ft	15	Enter data from instruction sheet
Average harvest speed	S	mph	4.0	Enter data from instruction sheet
Harvest efficiency	е	decimal	0.8	Enter data from instruction sheet
Effective Field Capacity	EFC	ac/hr	5.8	Enter formula in cell D10 using cell references
Corn Yield	Y	bu/ac	180	Enter data from instruction sheet
Maximum Harvest Rate	MHR	bu/hr	1047.3	Enter formula in cell D12 using cell references
Largest Vehicle Capacity	LV	bu	850	Enter data from instruction sheet
Smallest Vehicle Capacity	SV	bu	500	Enter data from instruction sheet
Farthest distance - field to grain center	FD	miles	1.1	Enter data from instruction sheet
Average travel speed - largest vehicle (full)	VL _{full}	mph	20	Enter data from instruction sheet
Average travel speed - largest vehicle (empty)	VL _{empty}	mph	35	Enter data from instruction sheet
Travel time to grain center - largest vehicle	TTG	min	3.3	Calculated results
Travel time return to field - largest vehicle	TTR	min	1.9	Calculated results
Miscellaneous activity time	TMA	min	7	Enter data from instruction sheet
Time to fill the smallest vehicle	Sfill	min	28.6	Calculated results
Time available to unload largest vehicle	AUT	min	16.5	Calculated results
Pit capacity	PCa	bu	450	Enter data from instruction sheet
Unloading capacity	UC	bu/hr	1,458	Calculated results

Color	Key	
-------	-----	--

Enter data from instruction sheet Enter formula using cell references Calculated results

CONTESTANT NAME _____

CONTESTANT SCHOOL _____

ENERGY SYSTEMS

Wiring an Aeration Fan Problem Solving/Skill

Instructions:

You will have 15 minutes to do this exercise. Ask for assistance if you're not sure what you are doing. A branch circuit is to be run from a service panel to a 115-volt aeration fan. Extend the branch circuit cable through a box connector clamp and connect it to the circuit breaker and neutral bus in the panel. Use proper wiring procedures and safe work habits.



Evaluation Score	e Sheet				
Items			Points	<u>8</u>	
			Possible	Earned	
Proper circuitry, wire colors, screw colors	•••••		12		
Proper stripping of conductors and cable jackets			5		
Proper connection of conductors			5		
Safe work habits			<u>3</u>		
	Total	25			

CONTESTENT NAME _____

CONTESTANT SCHOOL _____

Environmental and Natural Resource Systems

Residue Management Individual Problem Solving/Skill

Instructions:

You will have 15 minutes to do this exercise. You will need a calculator and PM 1701A (Residue Management and Cultural Practices – Resource Conservation Practices).

<u>Part 1</u>: The line-transect method is a practical field method of estimating the residue cover after any field operation. Using the 50-foot tape stretched diagonally across simulated crop rows, determine the percent residue cover (show your work next to the answer box below for partial credit):

Percent residue cover =



<u>Part 2:</u> Complete the table below. Calculate the residue losses from fall harvest to after planting for soybeans for each field operation/conditions in the table below using the tables from the "Residue Management & Cultural Practices" Iowa State University Extension bulletin provided. Assume "Fragile Residue" with minimum residue reduction due to seasonal, implement, or field operations.

Field Operation/ Condition	Reduction Factor (Table 2.)	X	Residue Cover Remaining After Each Operation	=	Final Residue Cover
Harvest	0.70	Х	100	=	70
Winter decomposition		X		=	
Anhydrous ammonia application knifed in using coil shanks		X		=	
Planting with a drill with fluted coulter attachments		X		=	

Part 3: Conservation tillage is defined to be any tillage/planting system which leaves at least 30 percent of the field surface covered with crop residue cover after planting has been completed. This can reduce erosion by at least 50 percent compared to a bare, fallow soil situation. For the field operation/conditions above, was conservation tillage accomplished? If not, what could be done to maintain a conservation tillage status?

Evaluation Score Sheet		
Items	Point Point	<u>s</u>
	Possible	Earned
Part 1: Proper residue cover determination using the line-transect method	12	
Part 2: Completion of conservation tillage table	9	
Part 3: Answer to conservation tillage question	4	
	25	

Iowa FFA Agricultural Mechanics Career Development Event 2007

State of Iowa DEPARTMENT OF EDUCATION Career Education Division Grimes State Office Building Des Moines, IA 50319 CONTESTANT NAME _____

CONTESTANT SCHOOL _____

ENRS SKILL

Residue Management Individual Problem Solving/Skill

Instructions:

You will have 15 minutes to do this exercise. You will need a calculator.

<u>Part 1</u>: The line-transect method is a practical field method of estimating the residue cover after any field operation. Using the 50-foot tape stretched diagonally across simulated crop rows, determine the percent residue cover (show your work next to the answer box below for partial credit):

Percent residue cover = $40 \pm 4\%$ (20 foot markings landing on residue X 2 (double for 50' tape) = 40%)

<u>Part 2:</u> Complete the table below. Calculate the residue losses from fall harvest to after planting for soybeans for each field operation/conditions in the table below using the tables from the "Residue Management & Cultural Practices" Iowa State University Extension bulletin provided. Assume "Fragile Residue" (**therefore use second column of values for percent breakdown**) with minimum residue reduction due to seasonal, implement, or field operations (**therefore use maximum value within the range given**).

Field Operation/ Condition	Reduction Factor (Table 2.)	X	Residue Cover Remaining After Each Operation		Final Residue Cover
Harvest	0.70	X	100	_	70
				-	
Winter decomposition	1.00	Х	70	=	70
Anhydrous ammonia application knifed in using coil shanks	0.65	Х	70	=	45.5
Planting with a drill with					
fluted coulter attachments	0.70	Х	45.5	=	31.8

<u>Part 3:</u> Conservation tillage is defined to be any tillage/planting system which leaves at least 30 percent of the field surface covered with crop residue cover after planting has been completed. This can reduce erosion by at least 50 percent compared to a bare, fallow soil situation. For the field operation/conditions above, was conservation tillage accomplished? If not, what could be done to maintain a conservation tillage status?

Yes. If more residue cover was desired, using coil shanks with coulters for the anhydrous ammonia application would change the final residue cover 49% (0.70 x 70%). Or the planting operation could also be changed to a drill with smooth coulters or ripple coulters (0.85 x 45.5% = 38.6%) to meet the minimum conservation tillage level of 30%. A combination of these two operations would results in even greater residue cover (0.70 x 70% = 49%, then 0.85 x 49% = 41.6%). Other operations could also be considered.

Evaluation Score Sheet		
Items	Points	
	Possible	Earned
Part 1: Proper residue cover determination using the line-transect method	12	
Part 2: Completion of conservation tillage table	9	
Part 3: Answer to conservation tillage question	<u>4</u>	
Total 25		

CONTESTENT NAME _____

CONTESTANT SCHOOL _____

INDUSTRY AND MARKETING SYSTEMS

Problem Solving/Skill Small Gasoline Engines

You are doing repair on a small gasoline engine that has been treated roughly. It is a Briggs and Stratton model series 133400 Type 0359 - 5 hp, single-cylinder. (An example of this engine is at the front of the room.)

In the repair process, you make the following measurement: Crankpin journal = 0.952 inches

Does the crankshaft need to be replaced? (check one):	🗆 Yes 🗆 No

You also notice that these items need to be replaced:

- magneto armature
- spark plug (you'll order two)
- air filter cartridge (you'll order two)
- engine gaskets
- carburetor gaskets

Using the Illustrated Parts List and Price sheet, determine the cost of the parts necessary to repair this engine. Complete the following table

Item	Part Number	Unit Cost (\$)	No. ordered	Price
Magneto armature				
Spark plug				
Air filter				
Engine gasket set				
Carburetor gasket set				
Crankshaft (may not be needed)				
			Subtotal	
			Tax (7%)	
Shipping			orders under \$20	
		\$8.70 for orders betw	een \$50 and \$100	
		\$12.50 for orders between	en \$100 and \$200	
			Total	

	Items	Poin	ts
		Possible	Earned
1.	Crankshaft replacement	5	
	Part numbers	6	
2.	Price and amount	6	
3.	Tax	2	
4.	Shipping	2	
5.	Total	3	
5.	Attitude and use of materials	<u>1</u>	
	Total	25	

CONTESTENT NAME

State of Iowa DEPARTMENT OF EDUCATION Career Education Division Grimes State Office Building Des Moines, IA 50319

INDUSTRY AND MARKETING SYSTEMS

Problem Solving/Skill Small Gasoline Engines

You are doing repair on a small gasoline engine that has been treated roughly. It is a Briggs and Stratton model series 133400 Type 0359 - 7.5 hp, single-cylinder. (An example of this engine is at the front of the room.)

In the repair process, you make the following measurement: Crankpin journal = 0.952 inches

Does the crankshaft need to be re	placed? (check one):	🗵 Yes 🗆 No

You also notice that these items need to be replaced:

- magneto armature
- spark plug (you'll order two)
- air filter cartridge (you'll order two)
- engine gaskets
- carburetor gaskets

KEY

Using the Illustrated Parts List and Price sheet, determine the cost of the parts necessary to repair this engine. Complete the following table

Item	Part Number	Unit Cost	No. ordered	Price
		(\$)		
Magneto armature	397358	\$38.25	1	\$38.25
Spark plug	802592	\$2.40	2	\$4.80
Air filter cartridge	494511	\$4.85	2	\$9.70
Engine gasket set	495661	\$11.25	1	\$11.25
Carburetor gasket set	498261	\$3.85	1	\$3.85
Crankshaft (may not be needed)	495645	\$66.20	1	\$66.20
			Subtotal	\$134.05
			Tax (7%)	\$9.38
Shipping		\$5	.25 for orders under \$50	\$12.50
			s between \$50 and \$100	
		\$12.50 for orders	between \$100 and \$200	
			Total	\$143.43

	Items	Poin	its
		Possible	Earned
	Crankshaft replacement	5	
	Part numbers	6	
2.	Price and amount	6	
3.	Tax	2	
4.	Shipping	2	
	Total	3	
5.	Attitude and use of materials	<u>1</u>	
	Total	25	

CONTESTENT NAME

State of Iowa DEPARTMENT OF EDUCATION Career Education Division Grimes State Office Building Des Moines, IA 50319

INDUSTRY AND MARKETING SYSTEMS

Problem Solving/Skill **Small Gasoline Engines**

You are doing repair on a small gasoline engine that has been treated roughly. It is a Briggs and Stratton model series 133400 Type 0359 – 7.5 hp, single-cylinder. (An example of this engine is at the front of the room.)

In the repair process, you make the following measurement: Crankpin journal = 0.952 inches

Does the crankshaft need to be re	placed? (check one):	🗵 Yes 🗆 No

You also notice that these items need to be replaced:

- magneto armature •
- spark plug (you'll order two) •
- air filter cartridge (you'll order two) •
- engine gaskets
- carburetor gaskets

KEY

Using the Illustrated Parts List and Price sheet, determine the cost of the parts necessary to repair this engine. Complete the following table

Item	Part Number	Unit Cost	No. ordered	Price
		(\$)		
Magneto armature	397358	\$38.25	1	\$38.25
Spark plug	802592	\$2.40	2	\$4.80
Air filter cartridge	494511	\$4.85	2	\$9.70
Engine gasket set	495661	\$11.25	1	\$11.25
Carburetor gasket set	498261	\$3.85	1	\$3.85
Crankshaft (may not be needed)	495645	\$66.20	1	\$66.20
	499764	\$7.55		
		· ·	Subtotal	\$134.05
			Tax (7%)	\$9.38
Shipping			.25 for orders under \$50	\$12.50
			s between \$50 and \$100	
		\$12.50 for orders	between \$100 and \$200	
			Total	\$155.93

	Items	Poir	its
		Possible	Earned
	Crankshaft replacement	5	
2.	Part numbers	6	
2.	Price and amount	6	
3.	Tax	2	
4.	Shipping	2	
5.	Total	3	
5.	Attitude and use of materials	1	
	Total	25	

Iowa FFA Agricultural Mechanics Career Development Event - 2007

State of Iowa Department of Education Career Education Division Grimes State Office Building Des Moines, IA 50319 CONTESTENT NAME _____

CONTESTANT SCHOOL _____

MACHINERY AND EQUIPMENT SYSTEMS

Combine and GPS Problem Solving/Skill

Instructions:

	bu have <u>15 minutes</u> to do this exercise. Using the sections from the owner's manual at your station, and your owledge of combines, answer the following questions.	
I.	What are the last 3 digits of the Product (Combine) Identification Number	1 pt.
II.	Identify by proper name the machine components and their function. Function a)	8 pts.
III.	. Determine the initial crop settings (standard cylinder) for corn and soybeans: Corn (dry, firm cob) Soybeans Cylinder Speed (RPM)	6 pts.
IV	 What openings are the chaffer, sieve, and extension indicators adjusted to (mm)? (DO NOT ADJUST) Chaffer mm Extension mm Sieve mm Are these settings properly adjusted for corn? (circle answer) Yes No 	4 pts.
V.	Where are these components of the yield monitoring system located on the combine? <u>Component</u> Location GPS receiver	3 pts.
VI	1.	2 pts.
PII Par Ini Ch Yie Yie	Evaluation Score Sheet Points Possible Earned N 1 rt Identification/Function 8 itial Crop Settings 6 naffer Sieve Adjustment 4 eld monitor components 3 eld monitor calibration 2 fety 1	
	Total 25	٦

Iowa FFA Agricultural Mechanics Career Development Event - 2007

State of Iowa Department of Education Career Education Division Grimes State Office Building Des Moines, IA 50319 CONTESTENT NAME <u>ANSWER KEY</u>

CONTESTANT SCHOOL _____

MACHINERY AND EQUIPMENT SYSTEMS

Combine and GPS Problem Solving/Skill

Instructions:

You have <u>15 minutes</u> to do this exercise knowledge of combines, answer the foll		m the owner's manual a	t your station, and your	
I. What are the last 3 digits of the Pro-	duct (Combine) Identifie	cation Number	435	1 pt.
 II. Identify by proper name the machin Name a) <u>tailings return elevator</u> b) <u>clean grain elevator</u> c) <u>moisture sensor</u> d) <u>front feederhouse drum adjustant</u> 		Function <u>returns unthreshed gr</u> <u>elevates grain to truc</u> <u>checks grain moistur</u>	ain to cylinder_ k	8 pts. rops
III. Determine the initial crop settings (aCylinder Speed (RPM)Concave Indicator settingsFan speed (RPM)	standard cylinder) for co <u>Corn (dry, firm cob)</u> 300-425 38-40 1100	orn and soybeans: Soybeans 300-480 14-38 1000		6 pts.
IV. What openings are the chaffer, sieve Chaffer <u>22</u> Sieve <u>17</u> Are these settings properly adjusted	mm _ mm	Extension	DO NOT ADJUST) 21 mm	4 pts.
V. Where are these components of the <u>Component</u> GPS receiver Yield sensor User interface		Location _top of grain tank/cab _inside top of clean gr _in cab, right post	roof ain elevator	3 pts.
VI. Name two components of the yield 1yield sensor	monitoring system that	should be calibrated price 2. <u>moisture sensor</u>	or to harvest.	2 pts.

Items	<u>Points</u>	-
	Possible	Earned
PIN	1	
Part Identification/Function	8	
Initial Crop Settings	6	
Chaffer Sieve Adjustment	4	
Yield monitor components	3	
Yield monitor calibration	,	_
Safety	1	
Тс	otal $2\overline{5}$	

CONTESTENT NAME _____

CONTESTANT SCHOOL _____

STRUCTURAL SYSTEMS

Problem Solving/Skills Grain Storage Structure Construction

Your task is to compute the amount of concrete needed for construction of a 27-foot diameter grain bin. The structure is pictured on the back of this sheet. Complete the following calculations to solve this problem.

1. Grain bin floor:

	a. Diameter of floor ft. Radius of floor ft.	(1 pts.)
	d. Cubic feet of floor cu.ft.	(3 pts.)
	c. Cubic yards of concrete for floor cu.yds. (Round up to nearest 0.5 cu.yds.)	(2 pts.)
2.	Grain bin foundation:	
	a. Cross-section size of foundation inches by inches	(1 pts.)
	b. Cubic feet of foundation cu.ft.	(3 pts.)
	c. Cubic yards of concrete for foundation cu.yds. (Round up to nearest 0.5 cu.yds.)	(2 pts.)
3.	Grain bin footing:	
	a. Cross-section size of footing inches by inches	(1 pts.)
	b. Cubic feet of footing cu.ft.	(3 pts.)
	c. Cubic yards of concrete for footing cu.yds. (Round up to nearest 0.5 cu.yds.)	(2 pts.)
4.	Total cubic yards of concrete for grain bin floor, foundation and footings cu.yds.	(2 pts.)
5.	Total cost of concrete at \$90.00 per cu.yd.: dollars (round up to the nearest \$)	(3 pts.)
	Evaluation Score Sheet	
	Items Points	
1.	Possible Earn Grain bin floor 6	

1.	Grain bin floor	6	
2.	Grain bin foundation	6	
2.	Grain bin footing	6	
3.	Total cubic yards of concrete	2	
4.	Total cost of concrete	3	
5.	Attitude and use of materials	2	
		$\frac{-}{25}$	
		_0	



CONTESTENT NAME <u>ANSWER KEY</u>

6

2

3

2

25

CONTESTANT SCHOOL _____

STRUCTURAL SYSTEMS

Problem Solving/Skills Grain Storage Structure Construction

Your task is to compute the amount of concrete needed for construction of a 27-foot diameter grain bin. The structure is pictured on the back of this sheet. Complete the following calculations to solve this problem.

1. Grain bin floor:

2.

3.

4.

5.

	a. Diameter of floor <u>26.5</u> ft. Radius of floor <u>13.25</u> ft.	(1 pts.)					
	d. Cubic feet of floor275.8cu.ft.	(3 pts.)					
	c. Cubic yards of concrete for floor <u>10.5</u> cu.yds. (Round up to nearest 0.5 cu.yds.)	(2 pts.)					
2.	Grain bin foundation:						
	a. Cross-section size of foundation <u>42</u> inches by <u>15</u> inches	(1 pts.)					
	b. Cubic feet of foundation <u>381.4</u> cu.ft.	(3 pts.)					
	c. Cubic yards of concrete for foundation <u>14.5</u> cu.yds. (Round up to nearest 0.5 cu.yds.)	(2 pts.)					
3.	Grain bin footing:						
	a. Cross-section size of footing <u>24</u> inches by <u>12</u> inches	(1 pts.)					
	b. Cubic feet of footing <u>174.6</u> cu.ft.	(3 pts.)					
	c. Cubic yards of concrete for footing <u>6.5</u> cu.yds. (Round up to nearest 0.5 cu.yds.)	(2 pts.)					
4.	Total cubic yards of concrete for grain bin floor, foundation and footings <u>31.5</u> cu.yds.	(2 pts.)					
5.	Total cost of concrete at \$90.00 per cu.yd.: <u>\$2835</u> dollars (round up to the nearest \$)	(3 pts.)					
Evaluation Score Sheet							
Items Points Points Earned							
1.	Possible Earn Grain bin floor 6						
2.	Grain bin foundation						

Grain bin footing.....

Total cubic yards of concrete

Total cost of concrete.....

Attitude and use of materials.....

.....Total



Iowa FFA Agricultural Mechanics Career Development Event 2007

State of Iowa DEPARTMENT OF EDUCATION Career Education Division Grimes State Office Building Des Moines, IA 50319 CONTESTANT NAME _____

CONTESTANT SCHOOL

ENRS SKILL

Residue Management Individual Problem Solving/Skill

Instructions:

You will have 15 minutes to do this exercise. You will need a calculator.

<u>Part 1</u>: The line-transect method is a practical field method of estimating the residue cover after any field operation. Using the 50-foot tape stretched diagonally across simulated crop rows, determine the percent residue cover (show your work next to the answer box below for partial credit):

Percent residue cover = $40 \pm 4\%$ (20 foot markings landing on residue X 2 (double for 50' tape) = 40%)

<u>Part 2:</u> Complete the table below. Calculate the residue losses from fall harvest to after planting for soybeans for each field operation/conditions in the table below using the tables from the "Residue Management & Cultural Practices" Iowa State University Extension bulletin provided. Assume "Fragile Residue" (therefore use second column of values for percent breakdown) with minimum residue reduction due to seasonal, implement, or field operations (therefore use maximum value within the range given).

Field Operation/ Condition	Reduction Factor	X	Residue Cover Remaining	=	Final Residue Cover
	(Table 2.)		After Each Operation		
Harvest	0.70	Х	100	=	70
Winter decomposition	1.00	Х	70	=	70
Anhydrous ammonia					
application knifed in using	0.65	Х	70	=	45.5
coil shanks					
Planting with a drill with					
fluted coulter attachments	0.70	Х	45.5	=	31.8

<u>Part 3:</u> Conservation tillage is defined to be any tillage/planting system which leaves at least 30 percent of the field surface covered with crop residue cover after planting has been completed. This can reduce erosion by at least 50 percent compared to a bare, fallow soil situation. For the field operation/conditions above, was conservation tillage accomplished? If not, what could be done to maintain a conservation tillage status?

Yes. If more residue cover was desired, using coil shanks with coulters for the anhydrous ammonia application would change the final residue cover 49% (0.70 x 70%). Or the planting operation could also be changed to a drill with smooth coulters or ripple coulters (0.85 x 45.5% = 38.6%) to meet the minimum conservation tillage level of 30%. A combination of these two operations would results in even greater residue cover (0.70 x 70% = 49%, then 0.85 x 49% = 41.6%). Other operations could also be considered.

Evaluation Score Sheet			
Items	<u>Points</u>		
	Possible	Earned	
Part 1: Proper residue cover determination using the line-transect method	12		
Part 2: Completion of conservation tillage table	9		
Part 3: Answer to conservation tillage question	<u>4</u>		
Total 25			